



# LAKESIDE FLOOD SOLUTIONS

LAKESIDE Puerta Anti  
Inundación & Cortafuegos de  
Acero



**PRODUCT DATA  
SHEET**

As Selected by CBRE & BT





**LAKESIDE**  
FLOOD SOLUTIONS

## LFS Puertas Anti Inundación & Cortafuegos de Acero

### Especificaciones:

- Protección robusta contra incendios e inundaciones
- Certificación Anti Inundaciones: Test BSI 1188-1:2009
- Certificación Cortafuegos: 4 horas, Test BS 476 Part 22: 1987
- Detalle Fábrica:

“Door Leaf double skinned with interlocking seams, reinforced vertically with interlocking channels and horizontally with tubes to prevent twisting. Spaces are filled with dense Rockwool. Astragal to leading edge”

“Door Frame formed to single rebated profile in welded form, reinforced and fitted with fixing plates. Fixings are sealed with rubber grommet”

## FICHA TÉCNICA

### Producto Único:

- Hoja: 1.5mm Acero Galvanizado; Grosor 45mm; Rockwool Core Infill
- Marco: 1.5mm Acero Galvanizado
- Threshold: Head Jamb Cill
- Hinge Type: Grade 13 Acero Inoxidable Ball Bearing Butt Hinges & Dog Bolt Butt Hinges (Welded). Complies with EN 1935:2002.
- Acabado: Factory Finish Etch Prime, Powder coating en cualquier color RAL
- Panic Ironmongery: Exidor 703B/30 - surface mounted three-point panic bolt for outward-opening single door applications
- Sellado: Unique Steel Flood Control Webbing complete with rubber seal



Interlocking channels



Panic Bolt



Dense Rockwool



Unique Steel Flood Control Webbing



OAD (Outside Access Device)



01792 561117

[sales@lakesidefloodsolutions.co.uk](mailto:sales@lakesidefloodsolutions.co.uk)

Bruce Road, Fforestfach Industrial Estate, Swansea SA5 4HS



[www.lakesidefloodsolutions.co.uk](http://www.lakesidefloodsolutions.co.uk)



Door closer (on all FR Doors)

3 point locking



Over panel doors

Removable mullion

Monkey bolts